

1 CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product Name G64130
Alternate Item Number G64130
MSDS Name BOSTIK'S BEST WDFL ADH
Generic Description Polyurethane Sealant/Adh
Manufacturer Bostik Findley, Inc.
211 Boston Street
Middleton , MA 01949 USA

24 Hour Emergency Assistance

Phone: 1-800-227-0332

General Assistance

Phone: 1-978-777-0100

MSDS Assistance

Phone: 1-978-777-0100

2 COMPOSITION / INFORMATION ON INGREDIENTS

| Component | CAS Number | Percentage |
|---|-------------|------------|
| Stoddard solvent | 8052-41-3 | 3 - 7 |
| Methylene Diphenyl Isocyanate (MDI) | 101-68-8 | 0.1 - 1 |
| Non-hazardous and other ingredients below reportable levels | Proprietary | Balance |

3 HAZARDS IDENTIFICATION

Emergency Overview

This product contains materials that on exposure could cause irritation and minor residual injury even if no treatment is provided. This product is stable under normal conditions but will react slightly with water to release some heat and carbon dioxide. The reaction is not violent.

POTENTIAL HEALTH EFFECTS

Skin Contact: Skin contact may cause irritation. A component of this product is a potential skin sensitizer. Repeated skin contact may cause a persistent irritation or dermatitis.

Eye Contact: May cause irritation with temporary redness with stinging and tearing.

Inhalation: Inhalation of hot mist may cause respiratory irritation. Prolonged or repeated exposure may cause asthmatic or other pulmonary responses.

Ingestion: Exposure is unlikely. This product can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

Target Organs

Skin. Eyes. Lungs.

4 FIRST AID MEASURES

Skin

Remove contaminated clothing to prevent further skin exposure and dispose of properly. In situations involving considerable skin contact, place the contaminated person in a deluge shower for at least 15 minutes. For minor exposures, wash thoroughly with soap and clean water. Get medical attention if irritation persists.

Eye

Immediately flush with plenty of water for at least 15 minutes, holding eyelids open at all times. Get medical attention immediately. See Notes to Physician.

Inhalation

Remove to fresh air. Give artificial respiration if not breathing. If symptoms persist, get medical attention.

Ingestion

No harmful effect is anticipated. If ingested, get immediate medical attention. Do not induce vomiting unless instructed to do so by medical personnel. If victim is conscious and not convulsing give 1 or 2 glasses of water to dilute the chemical. Never give anything by mouth to a victim who is unconscious or is having convulsions.

Notes To Physician

Treat symptomatically and supportively. Contact Bostik Findley to determine whether any additional information is available.

5 FIRE FIGHTING MEASURES

Extinguishing Media

Use dry chemical, carbon dioxide, or foam. Use water spray on large fires.

Dust Explosion Hazard

None Known

Sensitivity To Mechanical Impact

None Known

Sensitivity To Static Discharge

None Known

Unusual Fire & Explosion Hazards

This product is classified as a Combustible Liquid. Containers may explode in a fire. Product may burn and produce toxic gases in a fire.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective clothing including self contained breathing apparatus.

Flash Point > 142 F F (> 61 C)

6 ACCIDENTAL RELEASE MEASURES

Emergency Action

Appropriate safety measures and protective equipment should be used. See Section 8.

Containment

Isolate spill area. Stop discharge if safe to do so. Stop material from contaminating soil or from entering sewers or water streams. Scrape up polyurethane and deposit into appropriate containers.

7 HANDLING & STORAGE

For Commercial Use Only - Not Packaged or Labeled for Home Use!

Handling

Avoid contact with skin and eyes. Wash thoroughly after handling. Use this product with adequate ventilation.

Storage

Store in a clean, dry area. Keep containers closed.

Empty Container Precaution

Attention! Follow label warnings even after container is emptied since empty containers may retain product residues. Do not reuse empty container without professional cleaning for food, clothing, or products for human or animal consumption, or where skin contact can occur.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls

Use local exhaust ventilation when vapors, mists, or dusts can be released in concentrations above the TLV. Local exhaust is preferred, but general ventilation may be acceptable to meet exposure limits.

Eye Protection

Wear safety glasses with side shields.

Skin And Body Protection

Cover as much of exposed skin as possible. Wear protective clothing that provides protection against skin exposure. Wear chemical resistant gloves and clothing.

Respiratory Protection

Avoid breathing vapor and/or mists. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. High airborne concentrations may necessitate the use of self-contained breathing apparatus (SCBA) or a supplied air respirator.

General

Eyewash fountains and emergency showers should be readily available. Use good industrial hygiene practices in handling this material.

Exposure Limits

ACGIH - Occupational Exposure Limits - TWAs

| | | |
|--------------------------------------|-----------|---------------|
| Methylene bisphenol isocyanate (MDI) | 101-68-8 | 0.005 ppm TWA |
| Stoddard solvent | 8052-41-3 | 100 ppm TWA |

OSHA - Vacated PELs - Ceilings

| | | |
|--------------------------------------|----------|-------------------------------------|
| Methylene bisphenol isocyanate (MDI) | 101-68-8 | 0.02 ppm Ceiling; 0.2 mg/m3 Ceiling |
|--------------------------------------|----------|-------------------------------------|

OSHA - Vacated PELs - TWAs

| | | |
|------------------|-----------|----------------------------|
| Stoddard solvent | 8052-41-3 | 100 ppm TWA; 525 mg/m3 TWA |
|------------------|-----------|----------------------------|

9 PHYSICAL & CHEMICAL PROPERTIES

| | |
|---------------|---------------------------|
| Boiling Point | 310 - 405 F (154 - 207 C) |
|---------------|---------------------------|

| | | | |
|--------------|-------|--------------------|---------------------|
| MSDS Number | 25549 | Product | G64130 |
| Label Number | 25549 | NA = Not Available | ND = Not Determined |

| | |
|----------------------------|------------|
| Vapor Pressure | 2 MM HG |
| Vapor Density | 5 |
| Solubility In Water | 0 % |
| Target Solids | 93 % |
| pH | N/A |
| Density | 1.508 g/cc |
| Odor | Mild |
| Color | Amber |
| Physical State | Paste |
| Freeze Protect | No |

10 STABILITY & REACTIVITY

Stability/Incompatability

Stable under normal conditions.

Hazardous Reactions/Decomposition Products

If product is burned carbon monoxide, carbon dioxide, oxides of nitrogen, amines, isocyanate-containing compounds and other unknown products may be produced.

Hazardous Polymerization

Not likely to occur. However, curing of product releases carbon dioxide. If curing occurs inside a closed container, pressure buildup may result.

Conditions To Avoid

Avoid contact with Strong Oxidizers, Strong Alkalis, Strong Acids, Alcohols, and Water.

11 TOXICOLOGICAL INFORMATION

Ld50

NIOSH - Selected LD50s and LC50s

Methylene bisphenol isocyanate (MDI) 101-68-8 Oral LD50 Rat: 9200 mg/kg; Oral LD50 Mouse: 2200 mg/kg

Carcinogenicity

This product contains Methylene Diphenyl Isocyanate (MDI). MDI is not listed by the NTP, IARC or regulated by OSHA as a carcinogen. However, it has been shown to alter cells in certain experiments. Although inconclusive, these cellular changes are thought to indicate potential carcinogenicity.

12 ECOLOGICAL INFORMATION

VOC (Volatile Organic Compounds) 85 g/l

Ecotoxicological Information

Organic solvents produce slight to moderate toxicity to aquatic life. Insufficient data exists to evaluate the effect on plants, birds or land animals.

13 DISPOSAL CONSIDERATIONS

We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

Waste Disposal

This product is not known to be regulated under RCRA regulations but contains SARA regulated substances. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

14 TRANSPORT INFORMATION

| | |
|----------------------|----------------|
| Proper Shipping Name | Not Regulated |
| Hazard Class | Not Applicable |
| DOT Restrictions | Not Applicable |

15 REGULATORY INFORMATION

This MSDS is prepared and distributed pursuant to the Federal Hazard Communication Standard, 29 CFR 1910.1200.

Federal Regulations

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA - Hazardous Substances and their Reportable Quantities

Methylene bisphenol isocyanate (MDI) 101-68-8 5000 lb final RQ; 2270 kg final RQ

Based on an evaluation of the components used, this product does contain hazardous ingredients identified as per 29 CFR 1910.1200.

State Regulations

If this product contains any ingredients listed under California Proposition 65, they will be noted below:

International Regulations

This is a "controlled product" under the Canadian Workplace Hazardous Materials Information System (WHMIS). Class D Division 2 Sub-division B. and Class B Division 3

SARA 302 EXTREMELY HAZARDOUS SUBSTANCES

Not Regulated

SARA 311/312 HAZARD CATEGORIES

| | |
|-------------------|-----|
| Immediate Hazard | Yes |
| Delayed Hazard | Yes |
| Fire Hazard | Yes |
| Pressure Hazard | No |
| Reactivity Hazard | No |

SARA 313 TOXIC CHEMICALS

| Component | CAS Number | Percentage |
|-------------------------------------|------------|------------|
| Methylene Diphenyl Isocyanate (MDI) | 101-68-8 | 0.1 - 1 |

WHMIS RATINGS

WHMIS Status: Controlled

Immediate/Serious-VERY TOXIC - D1A

Other Toxic Effects-VERY TOXIC - D2A

Other Toxic Effects-TOXIC - D2B

Flammable/Combustible - B3

16 OTHER INFORMATION

Disclaimer

The data in this MSDS has been compiled from publicly available sources. This data relates only to the designated product and not to the use of said product in combination with other materials. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Responsibility for proper precautions and safe use of the product lies with the user. All data in this MSDS is typical of the product as a whole, and does not represent any individual lot or batch, therefore, Bostik Findley, Inc. makes no warranty about the accuracy of the data herein and assumes no liability for the use of such data. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

| | | | |
|--------------------|---------------|-------------------|-------------|
| Issue Date | 29-Apr-2004 | Supersedes | 16-Jan-2004 |
| Prepared By | Michael Simon | | |